

○ AVID SYSTEM-C In-wall Amplifier & Ceiling Speakers

Stylish, discreet wall-mounted stereo amplifier and ceiling speaker system. Ideal for AV and single room sound reinforcement systems and for integration with interactive whiteboards in the classroom or presentation suite/boardroom.

System Includes:

- Avid 2 x 6W stereo amplifier
- IR Remote Control
- Wallmounted Bracket for remote control
- Plugtop Power Supply
- 2 x FBT CSL106 Ceiling Speakers

Amplifier Features:

- Stereo amplifier fitted to UK 2-gang Wallplate
- Power handling 2 x 6W (RMS)
- 3 x Input Sources; Stereo Phono, 3.5mm Stereo Jack (Jack has priority) and Wired Input Terminal (on rear PCB)
- Line Level Sensitivity Switch
- Control of ON/OFF and volume via illuminated push button located on the front panel
- Infrared remote control of ON/OFF, volume, balance and tone facilities (supplied as standard)
- Clear LED level indicator / setting status display
- Screw terminations on the rear of the unit for loudspeakers, power and wired line input
- Separate loudspeaker balance adjustment to allow system set up (control located on rear of unit)
- Includes Plugtop Power Supply

Loudspeaker Features:

- Dual cone loudspeaker with 5" woofer
- Painted metal grille (White RAL 9016)
- Rated power 6W @ 8 ohm
- Fast fit solution



Amplifier Specifications:

Model:	Avid:
Output Power	2 x 6W @ 8Ω
Line Inputs	Stereo Phonos (L & R) Stereo 3.5mm Jack (priority) Screw Terminal (Rear PCB. In parallel with 3.5mm Jack Input)
Frequency Response	40Hz ~ 20KHz
Input Sensitivity	200mv / 1v
Power Requirements	24v DC, 1.25A
Dimensions	165(W) x 100(H) x 35(D) mm
Weight	0.26kg

Loudspeaker Specifications:

Model:	CSL106:
Rated Power	6W @ 8Ω
Frequency Response	100Hz ~ 20KHz
Sensitivity 1W/1m	93dB
Cut-out Diameter	145mm
Dimensions	175(Ø) x 60(D) mm
Weight	0.5kg