


CS 106 T

CEILING LOUSPEAKER



ø 170



ø 145

ABS recessed ceiling loudspeaker

- Dual cone loudspeaker
- Power 1.5, 3, 6W with 100V transformer
- Dispersion (-6dB) 1kHz/4kHz 130°/90°




CS 106 T


Rated power	1, 3, 6W with tapping switch
Loudspeaker	2-way dual cone, 4" woofer
Frequency response	100Hz~20kHz
Sensitivity 1W/1m	89dB
Maximum SPL 1m	97dB
Input voltage	100V
Weight	0.7kg
Dimensions	ø 170 x 70mm
Cut-out diameter	ø 145mm

CS 206 TCP

CEILING LOUSPEAKER



ø 213



ø 185

ABS recessed ceiling loudspeaker

- Steel mesh
- 2-way coaxial loudspeaker
- Power 1.5, 3, 6W with 100V transformer
- Dispersion (-6dB) 1kHz/4kHz 150°/80°
- ABS base




CS 206 TCP


Rated power	1, 3, 6W with tapping switch
Loudspeaker	2-way dual cone, 5 1/4" woofer with dome tweeter
Frequency response	50Hz~20kHz
Sensitivity 1W/1m	89dB
Maximum SPL 1m	97dB
Input voltage	100V
Weight	1.7kg
Dimensions	ø 213 x 115mm
Cut-out diameter	ø 185mm

CS 310 TCP

CEILING LOUSPEAKER



ø 240



ø 210

ABS recessed ceiling loudspeaker

- Steel mesh
- 2-way coaxial loudspeaker
- Power 1.25, 2.5, 5, 10W with 100V transformer
- Dispersion (-6dB) 1kHz/4kHz 160°/50°
- ABS base




CS 310 TCP


Rated Power	1.25, 2.5, 5, 10W with switch type regulator
Loudspeaker	2-way coaxial, 6.5" woofer with dome tweeter
Frequency response	50Hz~20kHz
Sensitivity 1W/1m	89dB
Maximum SPL 1m	99dB
Input voltage	100V
Weight	2.2kg
Dimensions	ø 240 x 156mm
Cut-out diameter	ø 210mm

CS 506 VA

CEILING LOUSPEAKER



ø 180



ø 160

ABS recessed ceiling loudspeaker with steel body

- Metal protective mesh white RAL9003 colour
- Fireproof steel base
- Ceramic connection terminal boards
- 150° thermal fuse
- Earth connection screw and internal wiring
- Complies with British Standard part 8 in alarm message diffusion systems
- Dual cone loudspeaker
- Power 6W with 100V transformer
- SPL 1W/1m 92dB
- Dispersion (-6dB) 1kHz/4kHz 130°/50°



CS 506 VA

Rated Power	6W
Loudspeaker	5.25" Dual cone speaker
Frequency response	100Hz~20kHz
Sensitivity 1W/1m	92dB
Maximum SPL 1m	99dB
Input voltage	100V
Weight	1.3kg
Dimensions	ø 180 x 123.5mm
Cut-out diameter	ø 160mm