

MEGA-CON-X® FIELD INSTALLABLE CONNECTORS

Part Number to Order

XX X XX-XX XG-T3XX

Connector Type: _____

23 - Cable End
24 - Panel Mount

Contact Size: _____

2 - #20

Contact Style: _____

80 - Crimp (Supplied loose)
81 - P/C Tail .187" (4.7) (Supplied assembled)
82 - Solder Cup (Supplied assembled)
91 - P/C Tail .280" (7.1) (Supplied assembled)*
92 - P/C Tail .335" (8.5) (Supplied assembled)*

Number of Contacts: _____

31

Type of Contact: _____

P - Pin
S - Socket

Contact Plating: _____

G - Gold over Nickel (Standard)

Back Shell Style 3

Grommet Code – Cable O.D. Range:
50 -.51 - .56 (12.9 - 14.2)

Back Shell Style:

3 Mechanical screw-down cable clamp with grommet seal and (1) interfacial "O" ring for cable end.

300 - Panel mount with hex nut & gasket.

3ES - 300 with Epoxy


Coupling Type

Blank - Twist Lock
T - Threaded

*Available in #20 size contact only.


Consult factory for your custom design cable assemblies and connectors. (See pages 3 & 26)

Contact Arrangements



31-#20

Quick Connect Type



31-#20

Threaded Type

Contact arrangements shown are wiring view of cable end pins/sockets.
Key/keyway shown for orientation only.